



TRUCK BED COATING

#20-41 Black

This product is a thick, durable black sealant that forms a protective skin that is both tough and flexible. Protects against corrosion and abrasion, withstands impacts, provides improved traction, and resists water. Truck Bed Liner greatly extends equipment and vehicle life expectancy.

Suggested Uses:

Truck beds
 Trailers
 Vehicle panels
 Wheel wells
 Repair existing liner coatings

Packaging:

| | |
|--------------------------|---------------------------|
| UPC Code | 043281008686 |
| Cans per case | 6 |
| Shipping weight per case | 18 lbs. |
| Container | 20 fluid ounce can |
| Label weight | 15 ounces (425 grams) |
| Shipping Classification | Limited quantity, UN 1950 |
| Hazard Class | 2.1 |

Properties:

| | |
|-------------------------|--------------------------|
| Coverage | Up to 15 square feet |
| Cleanup | Paint or lacquer thinner |
| Flammability | Extremely Flammable |
| Flash point | -4F |
| Specific Gravity | 0.80 |
| Solids Content | 21% |
| MIR value | 0.86, cannot exceed 0.95 |
| HAPs content | 18% |
| Storage Temperature | 40-90F |
| Application Temperature | 50-100F |
| Durability | Very Good |
| Abrasion Resistance | Very Good |
| Heat Resistance | 300F |
| Gasoline Resistance | No |
| Resin System | Polyurethane |
| Shelf life | Guaranteed for 2 years |

Dry Time*:

| | |
|-------------------|---------------|
| To touch | 30-45 minutes |
| To handle | 8-10 hours |
| Return to service | 24-36 hours |
| Full cure | ~4 days |

*At 72F, 50% humidity,
 1.5 mil thickness

Curing/Recoat time is extended with multiple coats, cool temperatures, lack of air flow, and excessively thick coats

Gloss*: Low Lustre, 15-25

*dependant on temperature/humidity/air flow

12-19-2021