



QUIET SEAL I #20-6 Black

An autobody undercoating for application to the undercarriage for rust protection and sound deadening. Asphalt base undercoating remains pliable and resists temperature extremes. Sprays evenly and dries completely to a smooth consistency. Does not sag and dries quickly.

Suggested Uses:

- Panel & fender undersides
- Hoods & decks
- Trunk interiors
- Section repairs
- Weld joints
- Rust holes
- All chassis parts

Packaging:

UPC Code	043281005197
Cans per case	12
Shipping weight per case	19.6 lbs.
Container	20 fluid ounce can
Label weight	18 ounces (511 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Extremely Flammable"
Flash point	-4° F
Specific Gravity	0.80
Solids Content	~40%
VOC content	~29%, cannot exceed 40%
MIR value	~0.30
HAPs content	4%
Storage Temperature	40-90F
Application Temperature	50-100F
Durability	Very Good
Abrasion Resistance	Very Good
Heat Resistance	300° F
Gasoline Resistance	No
Resin System	Petroleum Asphalt
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	10 minutes
To handle	6 hours

*At 72° F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick
 coats**

Gloss*: Low Lustre, 15-25

*as measured on a 60° gloss meter

12-1-2021