

## **TECHNICAL DATA SHEET**



## **TOOL CRIB SILICONE LUBE**

#620-1500

A clear silicone lubricant for use on all sliding and rubbing surfaces. Authorized by USDA for use in Federally inspected meat and poultry plants. Comes with an extension tube for pinpoint application, and sprays in any position. Withstands high pressures, does not stain, and has low odor.

## **Suggested Uses:**

Windows Doors Linkage Speedometer cables Shovels Chutes

Packaging:

UPC Code 043281006695

Cans per case 6 Shipping weight per case 9 lbs.

Container 20 fluid ounce can
Label weight 13 ounces (369 grams)
Shipping Classification Limited quantity, UN 1950

Hazard Class 2.

## **Properties:**

Cleanup Lacquer thinner Flammability Extremely Flammable

Flash point -4F Specific Gravity 0.80 Solids Content 5%

VOC content 59%, can't exceed 60%

HAPs content 39% 40-90F Storage Temperature Application Temperature 40-100F **Lubricity Rating** Excellent **Appearance** Clear Operating Speed 2000+ RPM High Temperature Resistance 400F Low Temperature Resistance -40F **Heavy Load Capability** 

Shelf life Guaranteed for 2 years
Food contact rating H1 (incidental food contact)

12-11-2021