

TECHNICAL DATA SHEET



TOOL CRIB DRY MOLY LUBE

#620-1505

A quick-drying, thin film that provides superior lubrication under extreme pressures and a broad temperature ranges. Excellent adhesion, oil free, and protects against seizing, fretting, and galling. Provides excellent antiwear protection for cutting and forming tools.

Suggested Uses:

Dust free lubricant for pre-assembly and production Wire drawing Gasket and stop-off coating Rubber mold release Machine tool slides Conveyors (hi-temperature)

Packaging:

UPC Code04328Cans per case6Shipping weight per case9 lbs.Container20 fluLabel weight14 ouShipping ClassificationLimiteHazard Class2.1

043281007023 6 9 lbs. 20 fluid ounce can 14 ounces (397 grams) Limited quantity, UN 1950 2.1

Properties:

Cleanup Flammability Flash point Specific Gravity Solids Content VOC content HAPs content Storage Temperature Application Temperature Active Ingredient Lubricity Rating Appearance Operating Speed High Temperature Resistent Low Temperature Resistent Heavy Load Capability Shelf Life	ce -100₀ F Yes
Shelf life Food contact rating	Guaranteed for 2 years No
i oou contact luting	

Dry Time:

Not Applicable

Gloss:

None

12-20-2021

Seymour of Sycamore | 917 Crosby Avenue | Sycamore |L 60178 Phone | 815.895.9101 • 800.435.4482 Fax | 815.895.8475 • 800.343.4258