1 Identification of the substance and manufacturer

HEAVY DUTY ANTI SEIZE

0006201507 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com 1-800-255-3924

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com

Emergency telephone number:

2 Hazard(s) identification

Classification of the substance or n		
Flammable Aerosols 1	H222 Extremely flammable aerosol.	
Gases under Pressure - Liquefied gas	H280 Contains gas under pressure; may explode if heated.	
Skin Irritation 2	H315 Causes skin irritation.	
Eye Irritation 2A	H319 Causes serious eye irritation.	
Toxic to Reproduction 1B	H360 May damage fertility or the unborn child.	
Specific Target Organ Toxicity - Single	Exposure 3 H336 May cause drowsiness or dizziness.	
Specific Target Organ Toxicity - Repea	ted Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.	
Additional information:		
GHS Hazard pictograms		
	GHS02 GHS04 GHS07 GHS08	
Signal word Hazard statements	Danger Extremely flammable aerosol.	
nazaru statements	Contains gas under pressure; may explode if heated.	
	Causes skin irritation.	
	Causes serious eye irritation.	
	May damage fertility or the unborn child.	
	May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.	
Precautionary statements	Obtain special instructions before use.	
r recutionary statements	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
	Do not spray on an open flame or other ignition source.	
	Pressurized container: Do not pierce or burn, even after use.	
	Do not breathe dust/fume/gas/mist/vapors/spray.	
	Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.	
	Wear protective gloves/protective clothing/eye protection/face protection.	
	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present	and
	easy to do. Continue rinsing.	
	Call a poison center/doctor if you feel unwell. Specific treatment (see on this label).	
	Take off contaminated clothing and wash it before reuse.	
	If eye irritation persists: Get medical advice/attention.	
	Store in a well-ventilated place.	
	Store locked up.	
	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations	<u>د</u>
		5.

3 Composition/information on ingredients

Chemical c Chemical D	haracterization: Mixtures escription:	This product is a mixture of the substances listed below with nonhazardous additions.		
Dangerous components:				
616-38-6	dimethyl carbonate		15-25%	
74-98-6	propane		15-25%	
67-64-1	Acetone		≥5-<10%	
106-97-8	n-butane		5-10%	
108-88-3	Toluene		≥5-<10%	
110-54-3			≥1-<5%	
64742-89-8	VM&P Naphtha		1-5%	

- 4 First-aid measures
 - After inhalation: After skin contact: After eye contact:

Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 2)

Revised On 01/06/2023

	(Contd. of page
After swallowing:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness
Indication of any immediate medic attention needed:	cal No further relevant information available.
5 Fire-fighting measures	
Extinguishing agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards:	Can form explosive gas-air mixtures.
Protective equipment for firefighters:	A respiratory protective device may be necessary.
6 Accidental release measures Personal precautions, protective	
equipment and emergency	
procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for	
containment and cleaning up:	Ensure adequate ventilation. Dispose contaminated material as waste according to section 13.
7 Handling and storage	
Precautions for safe handling Storage requirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up.
8 Exposure controls/personal pr	
	t require monitoring at the workplace:
74-98-6 propane PEL (USA) Long-term value: 1800 r	ng/m³ 1000 ppm
74-98-6 propane PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r	
PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r TLV (USA) see Appendix F Minimal	ng/m³, 1000 ppm
PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r TLV (USA) see Appendix F Minimal 67-64-1 Acetone	ng/m³, 1000 ppm oxygen content (D, EX)
PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r TLV (USA) see Appendix F Minimal 67-64-1 Acetone PEL (USA) PEL (USA) Long-term value: 2400 r	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)PEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 590 m	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pLong-term value: 250 p	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 p	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pLong-term value: 250 pA4, BEI106-97-8 n-butaneREL (USA)Long-term value: 1900 r	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm om
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pLong-term value: 250 pA4, BEI106-97-8 n-butaneREL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1900 r	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm om
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pLong-term value: 250 pA4, BEI106-97-8 n-butaneREL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1900 rTLV (USA)Short-term value: 1000 r	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm pm pm pm
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pLong-term value: 250 pA4, BEI106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1900 rTLV (USA)Short-term value: 200 pPEL (USA)Long-term value: 1000 (EX)	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm om ng/m³, 800 ppm ppm
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 500 pLong-term value: 500 pA4, BEI106-97-8 n-butaneREL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1900 rTLV (USA)CellPEL (USA)Long-term value: 1000 rCellCellPEL (USA)Long-term value: 200 ppCeiling limit value: 300;*10-min peak per 8-hr si	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 250 ppm pm pm pm m ng/m³, 800 ppm ppm
PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r TLV (USA) see Appendix F Minimal 67-64-1 Acetone PEL (USA) PEL (USA) Long-term value: 2400 r REL (USA) Long-term value: 500 p Long-term value: 500 p Long-term value: 500 p A4, BEI 106-97-8 n-butane REL (USA) Long-term value: 1900 r TLV (USA) Short-term value: 1900 r TLV (USA) Long-term value: 200 p (EX) Ceiling limit value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 500 p	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 250 ppm pm om ng/m³, 800 ppm ppm
PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r TLV (USA) see Appendix F Minimal 67-64-1 Acetone PEL (USA) PEL (USA) Long-term value: 2400 r REL (USA) Long-term value: 500 p Long-term value: 500 p Long-term value: 500 p A4, BEI 106-97-8 n-butane REL (USA) Long-term value: 1900 r TLV (USA) Short-term value: 1900 r TLV (USA) Long-term value: 200 p (EX) Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) REL (USA) Short-term value: 300; *10-min peak per 8-hr s Short-term value: 375 m	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 250 ppm pm om ng/m³, 800 ppm ppm
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 500 pLong-term value: 500 pA4, BEI106-97-8 n-butaneREL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1900 rTLV (USA)Ceiling limit value: 1000 rTLV (USA)Long-term value: 200 pcCeiling limit value: 300;*10-min peak per 8-hr sREL (USA)Short-term value: 560 rrLONG-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A4	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 250 ppm pm om ng/m³, 800 ppm ppm
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 500 pLong-term value: 500 pA4, BEI106-97-8 n-butaneREL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1000 rTLV (USA)Ceiling limit value: 200 pcCeiling limit value: 300;*10-min peak per 8-hr sREL (USA)Long-term value: 200 pcCeiling limit value: 300;*10-min peak per 8-hr sREL (USA)Short-term value: 375 mLV (USA)Long-term value: 20 prBEI, OTO, A4110-54-3 hexane	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 250 ppm pm om ng/m³, 800 ppm ppm om 500* ppm hift ig/m³, 150 ppm n
PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r TLV (USA) see Appendix F Minimal 67-64-1 Acetone PEL (USA) PEL (USA) Long-term value: 2400 r REL (USA) Long-term value: 500 p Cong-term value: 500 p Long-term value: 500 p A4, BEI 106-97-8 n-butane REL (USA) Long-term value: 1900 r TLV (USA) Short-term value: 1900 r TLV (USA) Long-term value: 1900 r TLV (USA) Long-term value: 200 pc (EX) 108-88-3 Toluene PEL (USA) Long-term value: 200 pc Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 300; *10-min peak per 8-hr s REL (USA) Long-term value: 375 m TLV (USA) Long-term value: 20 ppr BEI, OTO, A4 110-54-3 hexane PEL (USA) Long-term value: 1800 r	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 250 ppm pm om ng/m³, 800 ppm ppm om 500* ppm hift ig/m³, 150 ppm g/m³, 150 ppm n
PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r TLV (USA) see Appendix F Minimal 67-64-1 Acetone PEL (USA) PEL (USA) Long-term value: 2400 r REL (USA) Long-term value: 500 p Cong-term value: 500 p Long-term value: 500 p Ad, BEI 106-97-8 n-butane REL (USA) Long-term value: 1900 r TLV (USA) Short-term value: 1900 r TLV (USA) Long-term value: 1000 (EX) 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Long-term value: 375 m TLV (USA) Long-term value: 20 ppr BEI, OTO, A4 110-54-3 hexane PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 50 ppr BEI, OTO, A4 110-54-3 hexane PEL (USA) Long-term value: 180 m TLV (USA) Long-term value: 50 ppr	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 250 ppm pm om om om ppm ppm om s00° ppm ppm om s00° ppm hift ng/m³, 150 ppm g/m³, 150 ppm n
PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r TLV (USA) see Appendix F Minimal 67-64-1 Acetone PEL (USA) PEL (USA) Long-term value: 2400 r REL (USA) Long-term value: 500 p Cong-term value: 500 p Short-term value: 500 p A4, BEI 106-97-8 n-butane REL (USA) Long-term value: 1900 r TLV (USA) Short-term value: 1000 r TLV (USA) Long-term value: 1000 r TLV (USA) Long-term value: 200 pr Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Long-term value: 300; *10-min peak per 8-hr s Short-term value: 375 m LUV (USA) Short-term value: 20 pp BEI, OTO, A4 110-54-3 hexane PEL (USA) Long-term value: 20 pr BEI, OTO, A4 110-54-3 hexane PEL (USA) Long-term value: 1800 r REL (USA) Long-term value: 1800 r	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 250 ppm pm om om om ppm ppm ppm ppm ppm ppm
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 500 pLong-term value: 500 pLong-term value: 500 pA4, BEI106-97-8 n-butaneREL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1000 rTLV (USA)Short-term value: 1000 rTLV (USA)Long-term value: 200 pcCeiling limit value: 300; *10-min peak per 8-hr siREL (USA)Long-term value: 300; *10-min peak per 8-hr siREL (USA)Long-term value: 375 mTLV (USA)Long-term value: 20 ppr BEI, OTO, A4110-54-3 hexanePEL (USA)PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 50 ppr BEI, OTO, A4110-54-3 hexanePEL (USA)PEL (USA)Long-term value: 50 ppr Skin; BEIMineral OilPEL (USA)PEL (USA)Long-term value: 50 ppr	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm om ng/m³, 800 ppm ppm om 500* ppm hift ig/m³, 150 ppm g/m³, 150 ppm n n mg/m³, 500 ppm n
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 500 pLong-term value: 500 pLong-term value: 500 pAd, BEI106-97-8 n-butaneREL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1900 rTLV (USA)Long-term value: 1000 (EX)108-88-3 ToluenePEL (USA)Long-term value: 200 prCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300; *10-min peak per 8-hr sREL (USA)Long-term value: 375 mTLV (USA)Long-term value: 20 prBEI, OTO, A4Long-term value: 20 prBEI, OTO, A4Long-term value: 560 mLong-term value: 50 prBEI, OTO, A4110-54-3 hexanePEL (USA)PEL (USA)Long-term value: 180 mTLV (USA)Long-term value: 50 prSkin; BEIMineral OilPEL (USA)Long-term value: 50 prSkin; BEIMineral Oil	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm om form som som som som som som som som som pm n som soo pm n soo pm n soo pm n n n n n
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal67-64-1 AcetonePEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 500 pLong-term value: 500 pLong-term value: 500 pA4, BEI106-97-8 n-butaneREL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1000 rTLV (USA)Short-term value: 1000 rTLV (USA)Long-term value: 200 pcCeiling limit value: 300; *10-min peak per 8-hr siREL (USA)Long-term value: 300; *10-min peak per 8-hr siREL (USA)Long-term value: 375 mTLV (USA)Long-term value: 20 ppr BEI, OTO, A4110-54-3 hexanePEL (USA)PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 50 ppr BEI, OTO, A4110-54-3 hexanePEL (USA)PEL (USA)Long-term value: 50 ppr Skin; BEIMineral OilPEL (USA)PEL (USA)Long-term value: 50 ppr	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm om form som som som som som som som som som pm n som soo pm n soo pm n n n n n n n n
PEL (USA)Long-term value: 1800 rREL (USA)Long-term value: 1800 rTLV (USA)see Appendix F Minimal 67-64-1 Acetone PEL (USA)Long-term value: 2400 rREL (USA)Long-term value: 500 pLong-term value: 500 pLong-term value: 500 pAd, BEI 106-97-8 n-butane REL (USA)Long-term value: 1900 rTLV (USA)Short-term value: 1900 rTLV (USA)Long-term value: 1000 (EX) 108-88-3 Toluene PEL (USA)Long-term value: 200 prCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300; *10-min peak per 8-hr sREL (USA)Long-term value: 375 mTLV (USA)Long-term value: 20 prBEI, OTO, A4Long-term value: 20 prBEI, OTO, A4Long-term value: 500 prSkin; BEIMineral OilPEL (USA)Long-term value: 180 mTLV (USA)Long-term value: 10 mgKin; BEIMineral OilPEL (USA)Long-term value: 50 prSkin; BEIMineral OilPEL (USA)Long-term value: 50 prShort-term value: 50 prSkin; BEI	ng/m³, 1000 ppm oxygen content (D, EX) ng/m³, 1000 ppm g/m³, 250 ppm pm om form som som som som som som som som som pm n som soo pm n soo pm n soo pm n n n n n

Page 3/4

Revised On 01/06/2023

de name: HEAVY DUTY ANTI SEIZE		
Ingredient	s with biological limit valu	(Contd. of pag
67-64-1 Ac	*	163.
BEI (USA)		pecific)
108-88-3 T		· · ·
BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of v Parameter: Toluene	vorkweek
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene	
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with h	ydrolysis (background)
110-54-3 h		
BEI (USA)	0.5 mg/L Medium: urine Time: end of shift Parameter: 2.5-Hexanedior	ne without hydrolysis
Hygienic p Breathing Hand prot Eye protec	equipment: ection:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Store protective clothing separately. Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas cases where short and/or long term overexposure exists, a charcoal filter respirator should be we If you suspect overexposure conditions exist, please consult an authority on chemical hygeine. Nitrile gloves. The glove material must be impermeable and resistant to the substance. Tightly sealed goggles
Physical	and chemical properties	
Appearand Odor: Odor three	ce:	Aerosol. Aromatic Not determined.
pH-value: Melting po Boiling po	pint/Melting range	Not determined. Undetermined. -110 °C (-166 °F)
Flash poir Flammabi	nt: lity (solid, gas):	-19 °C (-2.2 °F) Extremely flammable.
-	sition temperature:	Not determined.
Auto ignit	-	Product is not self-igniting.
Lower Exp	explosion: blosion Limit: blosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol %
	ensity: sity on rate coefficient: n-octonal/wate	Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. r: Not determined.
Solubility: Viscosity: Water:		Not determined. Not determined. 0.0 %
Stability	and reactivity	
Reactivity	: s to avoid:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreez temperatures. Not fully evaluated.
Possibility	of hazardous reactions: ble materials:	No dangerous reactions known. No further relevant information available.
		(Contd. on pag

Page 4/4

Printing date 01/06/2023	Revised On 01/06/2023		
Trade name: HEAVY DUTY ANTI SEIZE			
Hazardous decomposition:	No dangerous decomposition products known. (Contd. of page 3)		
11 Toxicological information			
LD/LC50 values that are relevant for	classification:		
616-38-6 dimethyl carbonate			
Oral LD50 13,000 mg/kg (rat)			
Information on toxicological effects: Skin effects: Eye effects: Sensitization:	No data available. No irritant effect. No irritating effect. No sensitizing effects known.		
12 Ecological information			
12 Ecological information Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.		
Bioaccumulative potential: Mobility in soil: Remark: Other adverse effects:	No further relevant information available. No further relevant information available. Harmful to fish No further relevant information available.		
13 Disposal considerations Dispose of in accordance with local, sta disposed of responsibly. Do not heat or Recommendation: Recommended cleansing agent:	ate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be cut empty containers with electric or gas torches. Completely empty cans should be recycled. Water, if necessary with cleansing agents.		
14 Transport information			
UN-Number DOT	UN1950 UN1950 UN1950		
DOT Transport hazard class(es):	Aerosols, flammable		
Class Marine pollutant:	2.1 Gases No		
Special precautions for user:	Warning: Gases		
EMS Number:	F-D,S-Ŭ		
Packaging Group: UN "Model Regulation":	 UN1950, Aerosols, 2.1		
C			
15 Regulatory information			
SARA Section 355 (extremely hazard			
None of the ingredients in this product a	are listed.		
SARA Section 313 (Specific toxic che	emical listings):		
108-88-3 Toluene			
110-54-3 hexane Toxic Substances Control Act			
(TSCA):	All hazardous ingredients are found on the inventory list of substances.		
Canadian Domestic Substances List			
(DSL): Consumer Product Safety	All ingredients are listed or exempted.		
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
California Proposition 65 chemicals			
None of the ingredients in this product a			
Prop 65 chemicals known to cause b	irth defects or reproductive harm:		
108-88-3 Toluene 110-54-3 hexane			
EPA:			
67-64-1 Acetone			
110-54-3 hexane			
· · ·			
16 Other information			
Contact:	Regulatory Affairs		