

## TECHNICAL DATA SHEET





This is a specialized lightweight lubricant that both penetrates and protects against rust and corrosion. Displaces moisture, prevents flash rusting, and provides long term protection for metal. Does not contain silicone and meets following government specifications: MIL-C-16173D and MIL-C-23411 (metal corrosion test) and MIL-C-22235A (stain test).

## **Suggested Uses:**

Lubricates hinges, threads, and pulleys Loosen frozen nuts and bolts Replacement for WD-40 Coat metal parts that sit outside to protect from corrosion

Packaging:

UPC Code 043281007078

Cans per case 6

Shipping weight per case 9 lbs.

Container 20 fluid ounce can
Label weight 14 ounces (397 grams)
Shipping Classification limited quantity, UN 1950

Hazard Class 2.1

## **Properties:**

Coverage Up to 15 square feet Cleanup Lacquer thinner Storage Temperature 40-100F

Storage Temperature 40-100F Application Temperature 50-90F

Flammability Extremely Flammable

Specific Gravity 0.75
Solids Content ~20%

VOC content Does not exceed 25%

HAPs Content 0%
Lubricity Rating Excellent
Appearance light amber
Weather Resistance Excellent
Operating Speed 2000+ RPM

High Temperature Resistence
Low Temperature Resistence Heavy Load Capability
Shelf life Guaranteed for

150F
20F
No
2 years

12-2-2021