



TOOL CRIB SUPER STRENGTH PENETRATING OIL #620-1543

A lightweight penetrant that releases rusted, corroded or frozen assemblies. This fast acting formulation includes penetrants, lubricants, and corrosion inhibitors and leaves an anti-rust film for continued protection. Sprays in any direction and an extension tube is provided for pinpoint application.

Suggested Uses:

Freeing up:
 Fasteners
 Nuts
 Bolts
 Pins
 Valves
 Pipe couplings
 Machine parts

Packaging:

UPC Code	043281006873
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (426 grams)
Shipping Classification	Limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 20 square feet
Cleanup	Lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	23%
VOC content	47%, can't exceed 50%
HAPs content	3%
Storage Temperature	40-90F
Application Temperature	40-100F
Lubricity Rating	Excellent
Appearance	Clear
Weather Resistance	Excellent
Operating Speed	<500 RPM
High Temperature Resistance	150F
Low Temperature Resistance	-20F
Heavy Load Capability	No
Shelf life	Guaranteed for 2 years
Food contact rating	No

12-11-2021