1 Identification of the substance and manufacturer Trade name: TOOL CUTTING OIL Product code: 0006201557 Recommended use: Paint and coatings application. Uses advised against: Any that differs from the recommended use. Seymour of Sycamore Seymour of Sycamore Manufacturer/Supplier: 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com www.seymourpaint.com 1-800-255-3924 **Emergency telephone number:** 2 Hazard(s) identification Classification of the substance or mixture Flammable Aerosols 1 H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Skin Irritation 2 H315 Causes skin irritation. Eye Irritation 2A H319 Causes serious eye irritation. H335 May cause respiratory irritation. Specific Target Organ Toxicity - Single Exposure 3 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure. Additional information: **GHS Hazard pictograms** GHS02 GHS04 GHS07 GHS08 Signal word Danger Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. **Chemical Description:**

Dangerous components:		
74-98-6	propane	1-5%
106-97-8	n-butane	1-5%

4 First-aid measures			
After inhalation: After skin contact:	Supply fresh air; consult doctor in case of complaints. Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Wash exposed area with soap and water.		
After eye contact: After swallowing:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.		
Most important symptoms and effects:	Dizziness (Contd. on page 2)		

Printing date 01/06/2023

Page 2/4

Indication of any immediate medical attention needed:	(Contd. of page No further relevant information available.			
Fire-fighting measures				
Extinguishing agents: Special hazards:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.			
Protective equipment for firefighters:	A respiratory protective device may be necessary.			
Accidental release measures				
Personal precautions, protective				
equipment and emergency	Man protocility or view out. Know upperfected persons over			
procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.			
Methods and material for containment and cleaning up:	Ensure adequate ventilation.			
containment and cleaning up.				
Handling and storage				
Precautions for safe handling Storage requirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up.			
Exposure controls/personal prote	action			
Components with limit values that re				
74-98-6 propane				
PEL (USA) Long-term value: 1800 mg/	'm³, 1000 ppm			
REL (USA) Long-term value: 1800 mg/				
TLV (USA) see Appendix F Minimal ox	ygen content (D, EX)			
106-97-8 n-butane				
REL (USA) Long-term value: 1900 mg/ TLV (USA) Short-term value: 1000 ppr (EX)				
Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use.			
	Immediately remove all soiled and contaminated clothing. Wash hands after use.			
	Avoid contact with the eves and skin.			
Des ethics a service service	Do not eat or drink while working.			
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. cases where short and/or long term overexposure exists, a charcoal filter respirator should be wo			
	If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.			
Hand protection:	Nitrile gloves.			
Eye protection:	The glove material must be impermeable and resistant to the substance. Tightly sealed goggles			
Diversional and allowing the section				
Physical and chemical properties Appearance:	Aerosol.			
Odor:	Aromatic			
Odor threshold:	Not determined.			
pH-value: Melting point/Melting range Boiling point:	Not determined. Undetermined. -44 °C (-47.2 °F)			
Flash point: Flammability (solid, gas):	-19 °C (-2.2 °F) Extremely flammable.			
Decomposition temperature:	Not determined.			
Auto igniting:	Product is not self-igniting.			
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. Not determined. Not determined.			
Vapor pressure:	Not determined.			
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)			
Vapor density	Not determined.			
Evaporation rate	Not applicable.			
Partition coatticiant n. actonal/water				
Partition coefficient: n-octonal/water Solubility:	Not determined.			

Printing date 01/06/2023

Revised On 01/06/2023

Page 3/4

Trade nome: TOOL OUTTING OU						
Trade name: TOOL CUTTING OIL						
Viscosity:	Not determined. (Contd. of page 2)					
10 Stability and reactivity Reactivity: Conditions to avoid: Chemical stability: Possibility of hazardous reactions: Incompatible materials: Hazardous decomposition:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. Not fully evaluated. No dangerous reactions known. No further relevant information available. No dangerous decomposition products known.					
11 Toxicological information Information on toxicological effects Skin effects: Eye effects: Sensitization:	: No data available. Irritant to skin and mucous membranes. Irritating effect. No sensitizing effects known.					
42 Feelerical information						
12 Ecological information Aquatic toxicity: Persistence and degradability: Other information: Bioaccumulative potential: Mobility in soil:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents. No further relevant information available. No further relevant information available.					
Other adverse effects:	No further relevant information available.					
13 Disposal considerations Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.						
14 Tropoport information						
14 Transport information UN-Number DOT	UN1950 UN1950 UN1950					
DOT ADR Transport hazard class(es): Class Marine pollutant: Special precautions for user: EMS Number: Packaging Group: UN "Model Regulation":	Aerosols, flammable 1950 Aerosols 2.1 Gases No Warning: Gases F-D,S-U UN1950, Aerosols, 2.1					
15 Regulatory information SARA Section 355 (extremely hazardous substances): None of the ingredients in this product are listed. SARA Section 313 (Specific toxic chemical listings):						
None of the ingredients is listed. Toxic Substances Control Act (TSCA): Canadian Domestic Substances List (DSL): Consumer Product Safety	All hazardous ingredients are found on the inventory list of substances. All ingredients are listed or exempted.					
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.					
California Proposition 65 chemicals None of the ingredients in this product						
Prop 65 chemicals known to cause birth defects or reproductive harm:						
	•					
None of the ingredients is listed.	(Contd. on page 4)					

Revised On 01/06/2023

Trade name: TOOL CUTTING OIL				
EPA:		(Contd. of page 3)		
None of the ingredients is listed.				
16 Other information				
Contact:	Regulatory Affairs			