

TECHNICAL DATA SHEET



TOOL CRIB TOOLMAKER'S BLUE LAYOUT INK #620-1558

A smooth, cobalt blue coating that enables tool and die makers to scribe accurately without glare. Dries fast and will not rub off. Non-corrosive, resists heat, and eliminates the need for brushes and daubers. Can be easily and quickly removed with MRO Tool Crib® Layout Ink Remover, #620-1559.

Suggested Uses:

Sheet metal layouts Alignment of gears and worn drives Machined parts Production layout

Packaging:

UPC Code 043281007108

Cans per case 6 Shipping weight per case 9 lbs.

Container 20 fluid ounce can
Label weight 15 ounces (425 grams)
Shipping Classification limited quantity, UN 1950

Hazard Class 2.1

Properties:

Resin System

Coverage Up to 15 square feet
Cleanup Lacquer thinner
Flammability Extremely Flammable

Flash point -4F Specific Gravity 0.76 Solids Content 9%

MIR value 0.86, cant exceed 0.95

HAPs content 17%
Storage Temperature 40-100F
Application Temperature 50-90F
Durability Fair
Abrasion Resistance Good
Solvent Resistance No
Heat Resistance 300F

Shelf life Guaranteed for 2 years

Lacquer

Food contact rating No

Dry Time*:

5 minutes

*At 72F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*:

High Gloss, >80*

*as measured on a 60 degree gloss meter

12-11-2021