

# **TECHNICAL DATA SHEET**



## **BIG RIG PRIMERS**

#20-1607 Red Oxide, #20-1631 Light Gray

A rust proof industrial primer formulated specifically for use with the Big Rig Coatings. This high solids paint gives twice the coverage of conventional aerosol primers. Heat resistant, VOC compliant, and fast drying.

### **Suggested Uses:**

Rusted metal Restore equipment Refinish machinery Protect metal structures

Packaging:

UPC Code 20-1607 043281009164 20-1631 043281006590

Cans per case 6 Shipping weight per case 9 lbs.

Container 20 fluid ounce can
Label weight 17 ounces (482 grams)
Shipping Classification limited quantity, UN 1950

Hazard Class 2.1

#### **Properties:**

Coverage Up to 18 square feet
Cleanup Paint or lacquer thinner
Flammability Extremely Flammable

Flash point -4 F Specific Gravity 0.81 Solids Content 24%

MIR value 0.69, cannot exceed 0.70

HAPs content 11% Storage Temperature 40-100F Application Temperature 50-90F Heat Resistance 250F Resin System Phenolic

Shelf life Guaranteed for 2 years

Food contact rating N

#### **Dry Time\*:**

To touch 5 minutes

To recoat 20 minutes

\*At 72F, 50% humidity, 1.5 mil thickness

\*\*Curing/Recoat time is extended with multiple coats and excessively thick coats\*\*

Gloss\*: Flat, <15

\*as measured on a 60 degree gloss meter